

Network Engineering - Racks-PDU-Eficiencia Energetica

Network Enginnering España S.L.

PDU-1x32A.08C13+06C19

552,00€



POWER DISTRIBUTION UNIT (PDU)

INPUT

Amp (A)

1x32A.

Plug

IEC 60309 F+N+T
"Comando"

Cable
3 m.

OUTLETS

8 Outlets IEC320
C13 10A.

6 Outlets IEC320
C19 16A.

MAIN SPECIFICATIONS

Horizontal mount

Web & eMail Server

Monitor/Control depending on version type

SNMP v1 to v3. GET & SET Commands

C13 Outlet Anti-Fail

485 port for

[Discovery](#)

[NO-NC Alarm](#)

contact BMS

Test our Intelligent PDU range web interface and features

[Intelligent PDU Remote Access](#)

User *nee*

Password *nee*

SENSORS

Environment sensor input up to 8 sensor, any type

[Ambient](#), to choose from [Temperature / Humidity](#)

[Smoke](#)

[Water](#)

Intrusion

[Door](#)

DOCUMENTATION

[Product](#)

[Specification](#)

PRICES Price Version A1 Version Type - General

Monitoring (APC Metered)

[Vendor Information](#)

Customer Reviews: There are yet no reviews for this product.
Please log in to write a review.