

Network Engineering - Racks-PDU-Eficiencia Energetica

Network Engineering España S.L.

PDU-3x32A.18C13+06C19

729,00€



POWER DISTRIBUTION UNIT (PDU)

INPUT

Amp (A)

1x32A.

Plug

IEC 60309 F+N+T
"Comando"

Cable
3 m.

OUTLETS

18 Outlets IEC320
C13 10A.

6 Outlets IEC320
C19 16A.

MAIN SPECIFICATIONS

Vertical mount

C13 Outlet Anti-Fail

Web & eMail Server

485 port for

Monitor/Control depending on version type

[Voice chat](#)

SNMP (v1 to v3). GET & SET Commands

[No-NC Alarm](#)

contact BMS

Test our Intelligent PDU range web interface and features

Intelligent PDU Remote Access

User *nee*

Password *nee*

SENSORS

Environment sensor input up to 8 sensor, any type

[Combination](#), to choose from [Temperature / Humidity](#)

[Smoke](#)

[Water](#)

Intrusion

[Door](#)

DOCUMENTATION

[Product](#)

[Specification](#)

PRICES Price Version A1 Version Type - General

[Vendor Information](#) Monitoring (APC Metered)

Customer Reviews: There are yet no reviews for this product.

Please log in to write a review.